

Digital Hot Plate & Magnetic Stirrer AMTAST-PRO

เครื่องกวานสารให้ความร้อน AMTAST-PRO



Features :

- High accuracy of heating temperature controlling and the control of safe temperature
- Hotplate with porcelain enamel surface with excellent chemical resistance 2 adjustable safety circuits
- Separateness temperature sensor, protection temperature can be set
- Temperature sensor for heat transfer fluid and medium available (PT1000, Optional)
- Warning display indicating presence of any residual heat when the unit is switched off A,B,C Mode, ensure the stirring function not change due to external factors
- Bushing according to DIN 12878 for the use of contact thermometers

บริษัท โปรไทรอนิกส์ อินเตอร์เทรด จำกัด

38/40-41 หมู่ 3 ถนนลำลูกกา ตำบลคลุคต อำเภอลำลูกกา จังหวัดปทุมธานี

โทร. 02-5316293 (อัตโนมัติ) แฟกซ์. 02-5316294

www.ponpe.com

PRODUCT DATA SHEET

Specifications :

Voltage	100-120 / 200-240V
Frequency	50 / 60HZ
Power	550W
Stirring point position quantity	1
Max. stirring quantity (H2O)	20L
Stirring point position quantity	80mm
Motor type	External rotor brushless motor
Motor rating input	18W
Motor rating output	10W
Speed range	100-1500RPM
Speed display	LCD
Speed display accuracy	1RPM
Material	Porcelain enamel
Dimension of Plate	Ø135mm
Heating power	500W
Heat rate (1Lwater)	6K/min
Heating Temperature Range	RT-340C
Temperature display	LCD
Temperature display accuracy	0.1°C
Control accuracy of heating temperature	1°C
Adjustable safety circuit (heating plate)	100 - 350°C
Control accuracy of heating temperature with temperature	0.2°C
Temperature sensor of extra position	PT1000
Dimension	280×160×85mm
Weight	2.8 kg
Permissible ambient temperature	5-40°C
Permissible relative humidity	80%
Protection class acc. To DIN EN60529	IP42
RS232 interfaces	Yes