










Hand Held Temperature Probes

type K thermocouple

		order code	
penetration probe  Ø3.3 x 130 mm	This stainless steel penetration probe is strong, versatile and ideal for measuring liquids and semi-solids. <ul style="list-style-type: none"> • response time less than 3 seconds • probe temperature range -75 to 250 °C 	123-160 323-160 <i>(coiled lead)</i>	
penetration probe  Ø3.3 x 300 mm	This extended, stainless steel penetration probe is strong, versatile and ideal for measuring liquids and semi-solids. <ul style="list-style-type: none"> • response time less than 3 seconds • probe temperature range -75 to 250 °C 	123-168 323-168 <i>(coiled lead)</i>	
fast response probe  Ø3.3 x 100 mm	This reduced tip, fast response, stainless steel penetration probe is ideal for liquids or semi-solids i.e. soft rubber and other similar materials. <ul style="list-style-type: none"> • response time less than 2 seconds • probe temperature range -75 to 250 °C 	123-159 323-159 <i>(coiled lead)</i>	
needle penetration probe  Ø1.8 x 130 mm	This fast response, stainless steel needle penetration probe is ideal for liquids or semi-solids i.e. soft rubber or plastic. <ul style="list-style-type: none"> • response time less than 2 seconds • probe temperature range -75 to 250 °C 	123-100 323-100 <i>(coiled lead)</i>	
oven probe  Ø3.3 x 130 mm	This oven probe has a stainless steel handle and a two metre PTFE high temperature lead. An oven probe without a handle is available. <ul style="list-style-type: none"> • response time less than 4 seconds • probe temperature range -75 to 250 °C 	133-170 133-173 <i>(no handle)</i>	
rigid between pack probe  Ø4.5 x 130 mm	This rigid, stainless steel between pack probe is strong and versatile, designed specifically to measure between packets or boxes of produce. <ul style="list-style-type: none"> • response time less than 3 seconds • probe temperature range -75 to 250 °C 	123-060 323-060 <i>(coiled lead)</i>	
high temperature probe  Ø1.5 x 130 mm	This flexible, mineral insulated (MI) probe can be bent to any shape without affecting its performance. Ideal for measuring high temperatures i.e. fryers or furnaces. <ul style="list-style-type: none"> • response time less than 2 seconds • probe temperature range -200 to 1100 °C 	123-204 323-204 <i>(coiled lead)</i>	
high temperature probe  Ø3 x 130 mm	This flexible, mineral insulated (MI) probe can be bent to any shape without affecting its performance. Ideal for measuring high temperatures i.e. fryers or furnaces. <ul style="list-style-type: none"> • response time less than 2 seconds • probe temperature range -200 to 1100 °C 	123-212 323-212 <i>(coiled lead)</i>	
high temperature probe  Ø3 x 300 mm	The above flexible, mineral insulated (MI) probe is also available with an extended 300 mm probe.	123-213 323-213 <i>(coiled lead)</i>	

for type T thermocouple probes, replace the third digit (3) of the order code with the number 7