



Universal AC Power Source + AC Power Analyzer



Front (100W) and Rear (2000W) Universal Output Sockets For High Resolution Power testing to 10mW

Features:

- Low Power, high resolution front panel output with variable voltage and frequency
- HighPower rear panel output supplies line frequency and voltage
- Low Power Measurement (10mW to 100W) for testing power consumption of small devices or standby power at different voltages and frequencies
- High Power Measurement with Harmonics measurements 100mW to 1000W @ 110V or 100mW to 2000W @ 220V
- Power Quality Measurement (Watts, Power Factor, Voltage, Current, Harmonics)
- · Cost Function calculates cost per day, month, and year
- 99 memory locations for preset voltage and frequency output settings
- Standby and Operation button
- User-programmable Over Current Protection (current limiting)
- Programmable through the built-in RS-232 interface
- Data acquisition mode captures readings to your PC with a user-programmable sampling rate of 2 to 65,535 seconds
- Complete with AC power cord, RS-232 to USB cable and software



Concellan 2010/01/2/20 AP 11 2 Sept 24 1 4 Feb	
REAR	111.1
1	0.276
	60.00
	0.609
200	30.66
	18.69
the second s	24.30

Specifications	Range	Resolution	Accuracy	
Front Panel				
Output Voltage	85 to 250V (adjustable)	0.1V	±1%	
Output Frequency	45 to 65Hz (adjustable)	0.01Hz	±0.1Hz	
Power	10mW to 100W	0.1mW	$\pm(1\% + 0.05W)$	
AC Current	5mA to 1.5A	0.1mA	±1%	
Power Factor	0 to 1	0.001	±0.04	
Rear Panel				
Output Voltage	line voltage	0.1V	±1%	
Output Frequency	line frequency	0.01Hz	±0.1Hz	
Power	100mW to 2000W	0.1mW	$\pm(1\% + 0.5W)$	
AC Current	5mA to 10A	0.1mA	±1%	
Power Factor	0 to 1 0.001	±0.04		
Harmonics (in amps)	1 to 50th order	0.1mA	±1.4% (1-10th)	
THD	0.0 to 999.9%	0.1%		
Input Power Source	110 or 220V; 45 to 65Hz			
Dimension	12 x 10.2 x 5.9" (305 x 260 x 151mm)			
Weight	21.8lbs (9.9kg)			

contact:



sale@ponpe.com

Ordering Information:

380820Universal Power Supply + Power Analyzer

www.ponpe.com