

HI 9828 • GPS Multiparameter Meter



ORDERING INFORMATION

HI 9828 configurations are supplied with HI 769828 multisensor probe (pH/ORP, EC, DO, temperature), HI 9828-25 quick calibration standard solution (500 mL), probe maintenance kit, rechargeable C size Ni-MH batteries (4), power adapter & cable, car 12V accessory outlet adapter, HI 7698281 USB interface cable, HI 92828 Windows® compatible software and instruction manual in a rugged carrying case.

Choose your configuration below:

HI 982804-01	HI 9828 with GPS and 4 m (13.1') probe cable, 115VAC
HI 982804-02	HI 9828 with GPS and 4 m (13.1') probe cable, 230VAC
HI 9828010-01	HI 9828 with GPS and 10 m (33') probe cable, 115VAC
HI 9828010-02	HI 9828 with GPS and 10 m (33') probe cable, 230VAC
HI 9828020-01	HI 9828 with GPS and 20 m (66') probe cable, 115VAC
HI 9828020-02	HI 9828 with GPS and 20 m (66') probe cable, 230VAC
HI 9828030-01	HI 9828 with GPS and 30 m (98') probe cable, 115VAC
HI 9828030-02	HI 9828 with GPS and 30 m (98') probe cable, 230VAC
HI 9828040-01	HI 9828 with GPS and 40 m (131') probe cable, 115VAC
HI 9828040-02	HI 9828 with GPS and 40 m (131') probe cable, 230VAC
HI 9828050-01	HI 9828 with GPS and 50 m (164') probe cable, 115VAC
HI 9828050-02	HI 9828 with GPS and 50 m (164') probe cable, 230VAC
HI 9828060-01	HI 9828 with GPS and 60 m (200') probe cable, 115VAC
HI 9828060-02	HI 9828 with GPS and 60 m (200') probe cable, 230VAC
HI 9828070-01	HI 9828 with GPS and 70 m (230') probe cable, 115VAC
HI 9828070-02	HI 9828 with GPS and 70 m (230') probe cable, 230VAC
HI 9828080-01	HI 9828 with GPS and 80 m (262') probe cable, 115VAC
HI 9828080-02	HI 9828 with GPS and 80 m (262') probe cable, 230VAC
HI 9828090-01	HI 9828 with GPS and 90 m (295') probe cable, 115VAC
HI 9828090-02	HI 9828 with GPS and 90 m (295') probe cable, 230VAC
HI 98280100-01	HI 9828 with GPS and 100 m (328') probe cable, 115VAC
HI 98280100-02	HI 9828 with GPS and 100 m (328') probe cable, 230VAC

HI 9828/4-01	HI 9828 and 4 m (13.1') probe cable, no GPS, 115VAC
HI 9828/4-02	HI 9828 and 4 m (13.1') probe cable, no GPS, 230VAC
HI 9828/10-01	HI 9828 and 10 m (33') probe cable, no GPS, 115VAC
HI 9828/10-02	HI 9828 and 10 m (33') probe cable, no GPS, 230VAC
HI 9828/20-01	HI 9828 and 20 m (66') probe cable, no GPS, 115VAC
HI 9828/20-02	HI 9828 and 20 m (66') probe cable, no GPS, 230VAC
HI 9828/30-01	HI 9828 with GPS and 30 m (98') probe cable, no GPS, 115VAC
HI 9828/30-02	HI 9828 and 30 m (98') probe cable, no GPS, 230VAC
HI 9828/40-01	HI 9828 and 40 m (131') probe cable, no GPS, 115VAC
HI 9828/40-02	HI 9828 and 40 m (131') probe cable, no GPS, 230VAC
HI 9828/50-01	HI 9828 and 50 m (164') probe cable, no GPS, 115VAC
HI 9828/50-02	HI 9828 and 50 m (164') probe cable, no GPS, 230VAC
HI 9828/60-01	HI 9828 and 60 m (200') probe cable, no GPS, 115VAC
HI 9828/60-02	HI 9828 and 60 m (200') probe cable, no GPS, 230VAC
HI 9828/70-01	HI 9828 and 70 m (230') probe cable, no GPS, 115VAC
HI 9828/70-02	HI 9828 and 70 m (230') probe cable, no GPS, 230VAC
HI 9828/80-01	HI 9828 and 80 m (262') probe cable, no GPS, 115VAC
HI 9828/80-02	HI 9828 and 80 m (262') probe cable, no GPS, 230VAC
HI 9828/90-01	HI 9828 and 90 m (295') probe cable, no GPS, 115VAC
HI 9828/90-02	HI 9828 and 90 m (295') probe cable, no GPS, 230VAC
HI 9828/100-01	HI 9828 and 100 m (328') probe cable, no GPS, 115VAC
HI 9828/100-02	HI 9828 and 100 m (328') probe cable, no GPS, 230VAC

Longer probe cable lengths are available

QUICK CALIBRATION SOLUTIONS

HI 9828-25	Quick calibration solution, 500 mL
HI 9828-27	Quick calibration solution, 1 G

CLEANING AND MAINTENANCE SOL.

HI 70300L	Electrode storage solution, 500 mL
HI 7061L	Electrode cleaning solution, 500 mL

pH CALIBRATION SOLUTIONS

HI 7004L	pH 4.01 buffer solution, 500 mL
HI 7007L	pH 7.01 buffer solution, 500 mL
HI 7010L	pH 10.01 buffer solution, 500 mL

ORP CALIBRATION SOLUTIONS

HI 7021L	ORP test solution @240 mV, 500 mL
HI 7022L	ORP test solution @470 mV, 500 mL

DISSOLVED OXYGEN SOLUTIONS

HI 7040L	Zero oxygen solution, 500 mL
HI 7042S	Electrolyte solution, 30 mL

CONDUCTIVITY CALIBRATION SOL.

HI 7030L	12880 µS/cm solution, 500 mL
HI 7031L	1413 µS/cm solution, 500 mL
HI 7033L	84 µS/cm solution, 500 mL
HI 7034L	80000 µS/cm solution, 500 mL
HI 7035L	111800 µS/cm solution, 500 mL
HI 7039L	5000 µS/cm solution, 500 mL



SENSORS

HI 769828-0	pH sensor, single junction, non-refillable
HI 769828-1	pH/ORP sensor
HI 769828-2	DO sensor
HI 769828-3	EC sensor

OTHER ACCESSORIES

HI 7698281	USB interface cable
HI 7698282	Probe maintenance kit
HI 7698283	Calibration beaker
HI 7698284	Flow cell
HI 710045	Power supply cable
HI 710046	Lighter cigarette cable
HI 929828	Software application
HI 920005	iButton® with holder (5 pcs)

For a complete list of Solutions, see the end of pH Section 3, Conductivity Section 6, and Dissolved Oxygen Section 7.