



## HI96712 Aluminum Portable Photometer

- **CAL Check™**
  - Enables users to check validity of calibration
- **BEPS**
  - Alerts the user of low battery power that could adversely affect reading
- **GLP Features**
  - Meets Good Laboratory Practices

Aluminum is the most abundant metal and the third most abundant element in the Earth's crust, behind only oxygen and silicon. It is a lightweight, silvery metal, familiar to every household in the form of pots and pans, beverage cans, and aluminum foil. It is nontoxic, corrosion resistant, non-magnetic, and easy to form or cast into a variety of shapes.

In spite of the fact that aluminum is very active chemically, it does not corrode in moist air the way iron does. Instead, it quickly forms a thin, hard coating of aluminum oxide.

Aluminum is used in water purification because when it reacts with lime (or any base), it forms a sticky precipitate of aluminum hydroxide that binds tiny particles of impurities, thereby purifying the water.

The HI96712 measures the aluminum content in water and wastewater in the 0.00 to 1.00 mg/L range.

The meter uses an exclusive positive-locking system to ensure that the cuvette is in the same place every time it is placed into the measurement cell.

Specifications	HI96712 Aluminum
Range	0.00 to 1.00 mg/L (ppm)
Resolution	0.01 mg/L (ppm)
Accuracy @ 25°C (77°F)	±0.02 mg/L ±4% of reading
Light Source	tungsten lamp
Light Detector	silicon photocell with narrow band interference filter @ 525 nm
Power Supply	9V battery
Auto-off	after ten minutes of non-use in measurement mode; after one hour of non-use in calibration mode; with last reading reminder
Environment	0 to 50°C (32 to 122°F); RH max 95% non-condensing
Dimensions	193 x 104 x 69 mm (7.6 x 4.1 x 2.7")
Weight	360g (12.7 oz.)
Method	adaptation of the aluminon method
Ordering Information	<b>HI96712</b> is supplied with sample cuvettes (2) with caps, 9V battery, instrument quality certificate and instruction manual. <small>CAL Check™ standards and testing reagents sold separately</small>
	<b>HI96712C</b> includes photometer, CAL Check™ standards, sample cuvettes (2) with caps, 9V battery, cuvette wiping cloth, instrument quality certificate, instruction manual and rigid carrying case. <small>Reagents sold separately</small>
Reagents and Standards	<b>HI96712-11</b> CAL Check™ standard cuvettes
	<b>HI93712-01</b> reagents for 100 tests
	<b>HI93712-03</b> reagents for 300 tests

Standard reagents begin on page 10.70; CAL Check™ standard reagents begin on page 10.71

