LED



ppm

Free Chlorine

MW-10

MILWAUKEE

MW10/MW11

Low cost digital photometers to measure Free & Total Chlorine


Chlorine is the most commonly used water disinfectant. Applications vary from treatment of drinking water and wastewater to pool and spa sanitization and food processing to sterilization.

Milwaukee offers 2 models:

MW10 for measuring free chlorine (0.00 to 2.50 mg/L) and MW11 to measure total chlorine (0.00 to 3.50 mg/L).

Key features include:

- User friendly;
- Smaller & Ergonomic case design;
- Inexpensive;
- Larger and Easier to read Display;
- Good accuracy and immediate results;



Specifications MW10 **MW11** Free chlorine **Total chlorine** 0.00 to 2.50 ppm 0.00 to 3.50 ppm Range Resolution 0.01 ppm ±0.03 ppm ±3% of reading 0.01 ppm ±0.03 ppm ±3% of reading Accuracy (@25°C) Typical EMC Dev. Light Source ±0.01 ppm Light Emitting Diode @ 525 nm ±0.01 ppm Light Emitting Diode @ 525 nm Light Detector Method Silicon Photocell Adaptation of USEPA method Silicon Photocell Adaptation of USEPA method 330.5. The reaction betw 330.5. The reaction betw free chlorine and the DPD free chlorine and the DPD reagent causes a pink tint reagent causes a pink tint in the sample. 0 to 50°C (32 to 122°F) max. 95% RH non-condensing 1 x 1.5V AAA in the sample. 0 to 50°C (32 to 122°F) Environment max. 95% RH non-condensing 1 x 1.5V AAA Battery Type Auto-off after 2 minutes of non use 81.5 x 61 x 37.5 mm after 2 minutes of non use 81.5 x 61 x 37.5 mm Dimensions (3.2 x 2.4 x 1.5°) 64 g (2.25 oz.) (3.2 x 2.4 x 1.5°) 64 g (2.25 oz.) Weight



They are supplied with 2 cuvets, 6 reagents, a battery and instruction manual.



Accessories

Mi526-25 Free Chlorine powder reagent, (25 pcs) Mi524-25 Total Chlorine powder reagent (25 pcs)



Mi0011 Mi0013 Glass cuvets (2 pcs) Stoppers for cuvets (2 pcs)

Ordering information:

All handy photometers are supplied in a carton box including 2 cuvets, 6 powder reagents, 1 x 1.5 V AAA battery and instructions.