

DIGITAL CENTRIFUGE

MODEL : CN2200 / CN2060

FEATURE

- LED display speed and time.
- 10 memory programs for presetting parameters.
- Microprocessor controlled.
- Auto-accelerating and decelerating system.
- Auto cover-lid lock.
- Auto-braking system for presetting.
- Imbalance in the rotor shall cause power to be cut off.
- The buzzer will sound while centrifuge stops working.
- ABS hard shell and see-through window



Model	CN-2200	CN-2060
Speed (rpm)	1,000 ~ 8,000	500 ~ 6,000
Max. RCF (xg)	6,600	3,910
Max. Capacity (ml)	300	
Timer (min:sec)	99:59	
Weight (kg)	10	
Size (WxLxH mm)	290x320x250	
Power	AC 110V / 220V, 50/60Hz	

* Tubes not included.

ROTOR SETS FOR CN2200



Rotor	Capacity (ml x pcs)	Tube Size (Ø x L) mm	Max. Speed (rpm)	Max. RCF (xg)
RA-1508-1	15ml x 8	15~17.3 x 92~122	8,000	6,660
RA1512S-1	15ml x 12	15~17.3 x 92~122	7,000	5,320
RA-5004	50ml x 4	27.5~29.5 x 84~117	7,500	6,040
RA-5006	50ml x 6	27.5~29.5 x 84~117	7,000	5,260

ROTOR SETS FOR CN2060



Rotor	Capacity (ml x pcs)	Tube Size (Ø x L) mm	Max. Speed (rpm)	Max. RCF (xg)
RA-1508	15ml x 8	14~16.6 x 92~122	6,000	3,750
RA1512S	15ml x 12	14~16. x 92~122	6,000	3,910
RA-5004	50ml x 4	27.5~29.5 x 84~117	6,500	3,870
RA-5006	50ml x 6	27.5~29.5 x 84~117	6,000	3,870

PRODUCT DATA SHEET