



## **SK-D3309-Pro**

### **LCD Digital 3D Shaker**

#### **Features:**

- Three-dimensional rocking motion with an angle of 9°
- Max. load capacity is 5kg with platform
- Speed range of 10-70rpm
- Double LCDs for independent display time and speed
- Various of platforms accessories



## **SK-D1807-S**

### **LED Digital 3D shaker**

#### **Features:**

- Three-dimensional rocking motion with the angle of 7°
- Max. load capacity is 3kg with platform
- Speed range of 10-80rpm
- Double LCDs for independent display time and speed
- Various of platforms accessories



## **SK-D1807-E**

### **Economical 3D Shaker**

#### **Features:**

- Three-dimensional rocking motion with the angle of 7°
- Max. load capacity is 3kg with platform
- Speed range of 0-80rpm
- Wide range of platforms for use with a variety of vessels



Timer



Wide range of accessories



### Specifications

	SK-D3309-Pro	SK-D1807-S	SK-D1807-E
Tilt angle	9°	7°	7°
Max. load capacity (with platform)	5kg	3kg	3kg
Motor type	DC motor	DC motor	DC motor
Motor input power	40W	16W	16W
Motor output power	24W	10W	10W
Speed range	10-70rpm	10-80rpm	0-80rpm
Speed display	LCD	LED	scale
Timer display	LCD	LED	-
Time settings range	1min-19h59min	1min-19h59min	-
Voltage	100-240V,50/60Hz	100-240V,50/60Hz	100-240V,50/60Hz
Power	50W	20W	20W
Weight	9kg	2.7kg	2.7kg
Permissible ambient temperature and humidity	5-40°C, 80%	5-40°C, 80%	5-40°C, 80%
Dimensions[WxDxH]	360x430x106mm	270x330x130mm	270x330x130mm
Protection class	IP21	IP21	IP21
Data connector	-	-	-