



### TM-201 Light Meter

**Display :**

- 3<sup>1</sup>/<sub>2</sub> digits LCD with maximum reading 2000.
- Overload indication : "OL".
- Low battery indication : " ".

**Functions :**

- Data hold.
- Max.hold.
- Zero adjustment.
- Sensor : Silicon photo diode and filter.
- Meter size : 130x56x38mm. (LxWxH)
- Sensor size : 80x56x25mm. (LxWxH)
- Weight : 250g.

**Specifications :**

<b>Measuring range</b>	200, 2000, 20000, 200000 Lux 20,200, 2000, 20000 Foot-candle	
<b>Accuracy</b>	±3% (Calibrated to standard incandescent lamp 2856°K) ±8% (other visible light source )	
<b>Angle deviation from cosine characteristics</b>	10° 30° 50° 60° 80°	±0.5% ±2% ±3% ±6% ±25%

- According to JISC1609 : 1993 and CNS 5119 general A class specifications.
- Spectral response close to CIE luminous spectral efficiency.
- Measuring intensities of illumination in Lux or Foot-candle.
- Silicon photo diode and filter.
- Measuring light source include all visible light source.
- Length of wire for light sensor : approximately 1.5M.
- Cosine angular corrected.

**Functions :**

- Data hold.
- DC analog output.
- Max / Min hold.
- Zero adjustment.
- Sensor : Silicon photo diode and filter.

### TM-202 Light Meter



**Specifications :**

<b>Measuring range</b>	20,200, 2000, 20000, 200000 Lux 20,200, 2000, 20000 Foot-candle	
<b>Accuracy</b>	±3% (Calibrated to standard incandescent lamp 2856°K) ±6% (other visible light source )	
<b>Angle deviation from cosine characteristics</b>	10° 30° 50° 60° 80°	±0.5% ±2% ±3% ±6% ±25%

Applications include :warehouses, factories, office buildings, restaurants,schools, library, hospitals, photographic, video, parking garages, museums, art galleries, stadiums, building security.

## TM-720 Mini Pocket Light Meter (Auto - Ranging)



**Display :**

- 3 3/4 digits LCD with maximum reading 3999.
- Overload indication : "OL".
- Low battery indication : " ".

**Features :**

- According to JISC1609 : 1993 and CNS 5119 general A class specifications.
- Spectral response close to CIE luminous spectral efficiency.
- Measuring intensities of illumination in unit of Lux or Foot-candle.
- Silicon photo diode and filter.
- Cosine angular corrected.
- Max/Min/AVG hold.
- Measuring light source include all visible light source.
- Auto power off with disable function.
- Real Zero function.
- Auto ranging.
- Data hold.

**Specifications :**

<b>Accuracy</b>	±3% ±3Lux (0~500Lux) ±3% (up 501 Lux) (Calibrated to standard incandescent lamp 2856°K) ±8% (other visible light source)	<b>Measuring range</b>	40/400/4,000/40,000/400,000 Lux 40/400/4,000/40,000 Foot-candel
		● <b>Meter size</b> : 133 x48 x23mm.(LxWxH)	
		● <b>Power</b> : 2 batteries 1.5V AAA	
		● <b>Weight</b> : 80g (including battery)	